

MONBAT EFB + C E856CX0_1 235 Ah

According to EN 50342



Electrical specification

Voltage:	12V
Capacity C²⁰:	235 Ah
Cold cranking current:	1250 A [EN]
Cold cranking current:	730 A [DIN]

Mechanical specification

Dimensional group:	C
ETN reference:	735 002 125 EFB
DIN reference:	73502
Dimensions^A in mm (LxWxH):	514x276x242
Cell Layout:	3
Terminal Type:	1

Container

Case	Material	Polypropylene
	Bottom hold-down	B0
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Grey

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Grey

Handles	Material	Polypropylene
	Position	Sides - on container
	Colour	Black


Battery classification as per EN 50342-6

Water consumption	Charge retention	Vibration resistance	Endurance Level
W4	C2	V3	E3

Weight^B

Battery weight in kg:	41.45
Acid weight in kg:	19.50
Total battery weight in kg:	60.95

Layout



Hold-down



Separator

Type	PE
-------------	-----------

A. Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
B. Weight may vary ±5%.